



Database Programming with SQL

13-1

Creating Tables



Objectives

In this lesson, you will learn to:

- List and categorize the main database objects
- Review a table structure
- Describe how schema objects are used by the Oracle database
- Create a table using the appropriate data type for each column
- Explain the use of external tables
- Query the Data Dictionary to obtain the names and other attributes of database objects

Purpose

- Up until now, you have selected, updated, inserted, and deleted information in the existing tables of a database.
- As a Database Administrator (DBA), you will be expected to know how to create tables as well.
- In this lesson, you will learn which database objects are most frequently used, how to look at the table structure, and how to create new tables.

Purpose

- Your tables will be small compared to tables that hold millions of rows and hundreds of columns, but creating a small table involves the same SQL statements and syntax as creating a very large one.
- You will also learn about external tables—tables which are similar in structure to the normal Oracle database tables, but the actual data rows are stored externally in a flat file and are accessed only when needed.

Database Schema Objects

- An Oracle Database can contain many different types of objects.
- This section introduces the most commonly used objects, and also describes how the Oracle Server uses the information stored in the Data Dictionary when it is performing work as a result of the SQL statements you issue.

Database Schema Objects

- The main database object types are:
 - Table
 - Index
 - Constraint
 - View
 - Sequence
 - Synonym
- Some of these object types can exist independently and others can not.

Database Schema Objects

- Some of the object types take up space, known as storage, in the database and others do not.
- Database objects taking up significant storage space are known as Segments.
- Tables and Indexes are examples of Segments, as the values stored in the columns of each row take up significant physical disk space.
- Views, Constraints, Sequences, and Synonyms are also objects, but the only space they require in the database is in the definition of the object—none of them have any data rows associated with them.

Database Schema Objects

- The database stores the definitions of all database objects in the Data Dictionary, and these definitions are accessible to all users of the database as well as to the database itself.
- Have you ever wondered how Oracle knows which columns to return from a Query?
- For example, if you specify `SELECT * FROM jobs` instead of `SELECT job_id, job_title FROM jobs`, how does Oracle know which columns to return?
- The database looks up the definition of the table used in the query, translates the '*' into the full list of columns, and returns the result to you.

Database Schema Objects


- The database uses the Data Dictionary for all statements you issue, even if you list the column names instead of using '*'.
- It checks that the tables you are referencing in your statement exist in the database, it checks that the column names are correct, it checks if you have the correct privileges to perform the action you are requesting, and finally it uses the Data Dictionary to decide the Execution Plan – how it will actually perform the request.

Database Schema Objects

- The Data Dictionary itself can be queried by all database users.
- In Application Express, it can be accessed both via SQL statements in the SQL Workshop> SQL Commands interface and also from the SQL Workshop> Object Browser interface.

Database Schema Objects

- In the SQL Commands window, you have to know the names of the table you are querying, and in the Object Browser interface, you simply click on the listed objects to see their details.



The screenshot shows the Oracle Application Express interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', and 'Administration'. The 'SQL Workshop' tab is active, and the 'Object Browser' is open. The schema is set to 'US_A009EMEA815_PLSQL_T01'. On the left, a list of tables is shown, including F_FOOD_ITEMS, F_ORDERS, F_ORDER_LINES, F_PROMOTIONAL_MENUS, F_REGULAR_MENUS, F_SHIFTS, F_SHIFT_ASSIGNMENTS, F_STAFFS, GM_DEPT, GRADE_CHANGES, HTMLDB_PLAN_TABLE, IMR_ACTORS, IMR_MEDIA, IMR_MEMBERS, IMR_MOVIES, and IMR_RENTAL_HISTORIES. The 'JOBS' table is selected, and its structure is displayed in a table format.

Column Name	Data Type	Nullable	Default	Primary Key
JOB_ID	VARCHAR2(10)	No	-	1
JOB_TITLE	VARCHAR2(35)	No	-	-
MIN_SALARY	NUMBER(6,0)	Yes	-	-
MAX_SALARY	NUMBER(6,0)	Yes	-	-

Database Schema Objects

- So if you want to see the details of the JOBS table, you simply click on its title in the table listing:

The screenshot shows the Oracle Application Express interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', and 'Administration'. The 'SQL Workshop' tab is active, and the 'Object Browser' is displayed. The schema is set to 'US_A009EMEA815_PLSQL_T01'. On the left, a list of tables is shown, with 'JOBS' selected. The main area displays the 'JOBS' table details, including a table listing columns and their properties.

Column Name	Data Type	Nullable	Default	Primary Key
JOB_ID	VARCHAR2(10)	No	-	1
JOB_TITLE	VARCHAR2(35)	No	-	-
MIN_SALARY	NUMBER(6,0)	Yes	-	-
MAX_SALARY	NUMBER(6,0)	Yes	-	-

Database Schema Objects

- In this example using the Object Browser, you can see the details of the JOBS table as well as the options to view the data, indexes, constraints, grants, and other details of the table.

The screenshot shows the Oracle Application Express interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', and 'Administration'. The 'SQL Workshop' tab is active, and the 'Object Browser' is selected. The schema is set to 'US_A009EMEA815_PLSQL_T01'. On the left, a list of tables is shown, with 'JOBS' selected. The main area displays the 'JOBS' table details, including a table of columns and their properties.

Column Name	Data Type	Nullable	Default	Primary Key
JOB_ID	VARCHAR2(10)	No	-	1
JOB_TITLE	VARCHAR2(35)	No	-	-
MIN_SALARY	NUMBER(6,0)	Yes	-	-
MAX_SALARY	NUMBER(6,0)	Yes	-	-

Database Schema Objects

- Using the SQL Commands window, you must ask for a DESCription of the table.
- All the extra options offered by Object Browser are not available in this interface.

```
DESCRIBE jobs;
```

Results Explain Describe Saved SQL History

Object Type TABLE Object JOBS

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
JOBS	JOB_ID	VARCHAR2	10	-	-	1	-	-	Primary key of jobs table.
	JOB_TITLE	VARCHAR2	35	-	-	-	-	-	A not null column that shows job title, e.g. AD_ FI_ACCOUNTANT
	MIN_SALARY	NUMBER	-	6	0	-	✓	-	Minimum salary for a job title.
	MAX_SALARY	NUMBER	-	6	0	-	✓	-	Maximum salary for a job title

Table Creation

- All data in a relational database is stored in tables.
- When creating a new table, use the following rules for table names and column names:
 - Must begin with a letter
 - Must be 1 to 30 characters long
 - Must contain only A - Z, a - z, 0 - 9, _ (underscore), \$, and #
 - Must not duplicate the name of another object owned by the same user
 - Must not be an Oracle Server reserved word

Naming Conventions

- It is best to use descriptive names for tables and other database objects.
- If a table will store information about students, name it STUDENTS, not PEOPLE or CHILDREN.
- Table names are not case sensitive.
- For example, STUDENTS is treated the same as STuDents or students.



Naming Conventions

- Table names should be plural, for example STUDENTS, not student.
- Creating tables is part of SQL's data definition language (DDL).
- Other DDL statements used to set up, change, and remove data structures from tables include ALTER, DROP, RENAME, and TRUNCATE.



CREATE TABLE

- To create a new table, you must have the CREATE TABLE privilege and a storage area for it.
- The database administrator uses data control language (DCL) statements to grant this privilege to users and assign a storage area.
- Tables belonging to other users are not in your schema.
- If you want to use a table that is not in your schema, use the table owner's name as a prefix to the table name:

```
SELECT *  
FROM mary.students;
```

- You must be granted access to a table to be able to select from it.

CREATE TABLE Syntax

- To create a new table, use the following syntax details:
 - table is the name of the table
 - column is the name of the column
 - Data type is the column's data type and length
 - DEFAULT expression specifies a default value if a value is omitted in the INSERT statement

```
CREATE TABLE table
(column data type [DEFAULT expression],
(column data type [DEFAULT expression],
(.....[ ] );
```

CREATE TABLE Example


- The examples below show the CREATE TABLE statement:

```
CREATE TABLE my_cd_collection
(cd_number NUMBER(3),
 title VARCHAR2(20),
 artist VARCHAR2(20),
 purchase_date DATE DEFAULT SYSDATE);
```

```
CREATE TABLE my_friends
(first_name VARCHAR2(20),
 last_name VARCHAR2(30),
 email VARCHAR2(30),
 phone_num VARCHAR2(12),
 birth_date DATE);
```


External Tables

- Oracle also supports another table type: External table.
- In an external table, the data rows are not held inside the database files but are instead found in a flat file, stored externally to the database.
- Typically an external table is used to store data migrated from older versions of the databases used by a company.




External Tables

- When a company is implementing a new application and database, they typically need to import most of the data from the old systems to the new system for normal read and write access, but there may be some data that is not used frequently and therefore would only need to be accessed for read access.
- This kind of data could be held in an external table.



External Tables

- One of the many benefits for Oracle is that data held in external tables only has to be backed up once, and then never again unless the contents of the file change.
- The syntax to create an external table is very similar to that of creating a standard table, except that it has extra syntax at the end.



External Tables

- The new syntax (shown in red) on the following slides, is not used in standard SQL statements for table creation.
- ORGANIZATION EXTERNAL -- tells Oracle to create an external table
- TYPE ORACLE_LOADER -- of type Oracle Loader (an Oracle Product)
- DEFAULT DIRECTORY def_dir1 -- the name of the directory for the file

External Tables


- ACCESS PARAMETERS -- how to read the file
- RECORDS DELIMITED BY NEWLINE -- how to identify the start of a new row
- FIELDS – the field name and data type specifications
- LOCATION – name of the actual file containing the data
- An example of the new syntax is found in red on the next slide.

External Tables Example

```
CREATE TABLE emp_load
  (employee_number CHAR(5),
   employee_dob CHAR(20),
   employee_last_name CHAR(20),
   employee_first_name CHAR(15),
   employee_middle_name CHAR(15),
   employee_hire_date DATE)
ORGANIZATION EXTERNAL
  (TYPE ORACLE_LOADER
   DEFAULT DIRECTORY def_dir1
   ACCESS PARAMETERS
   (RECORDS DELIMITED BY NEWLINE
    FIELDS (employee_number CHAR(2),
           employee_dob CHAR(20),
           employee_last_name CHAR(18),
           employee_first_name CHAR(11),
           employee_middle_name CHAR(11),
           employee_hire_date CHAR(10) date_format DATE mask
           "mm/dd/yyyy" ))
   LOCATION ('info.dat'));
```


Data Dictionary

- Two kinds of tables exist in an Oracle Database: User tables and Data Dictionary tables.
- You can issue SQL statements to access both kinds of tables—you can select, insert, update, and delete data in the user tables, and you can select data in the Data Dictionary tables.




Data Dictionary

- User tables created by you containing your data:
 - employees, departments, jobs, etc.
- Data Dictionary tables:
 - DICTIONARY, USER_OBJECTS, USER_TABLES, USER_SEGMENTS, USER_INDEXES, etc.




Data Dictionary

- The Data Dictionary tables are all owned by a special Oracle user called SYS and only SELECT statements should be used when working with any of these tables.
- To make these tables safe from accidental user access, they all have views created through which the Data Dictionary is accessed by database users.



Data Dictionary

- If any Oracle user attempts to do inserts, updates, or deletes against any of the Data Dictionary tables, the operation is disallowed as it might compromise the integrity of the entire database.



Data Dictionary

- When you are using the Data Dictionary views in the SQL Commands interface, you need to know the names of the Dictionary views you are working with.
- In Oracle, this is quite simple: prefix the object type you are looking for with a USER_XXX or an ALL_XXX, where XXX is the object type.

```
SELECT table_name, status  
FROM USER_TABLES;
```

```
SELECT table_name, status  
FROM ALL_TABLES;
```


Data Dictionary

- So if you want to investigate indexes, then simply select from `USER_INDEXES`; if you want information about sequences, then the table is `USER_SEQUENCES` and so on.

```
SELECT *  
FROM user_indexes;
```

```
SELECT *  
FROM user_objects  
WHERE object_type = 'SEQUENCE';
```

Terminology

Key terms used in this lesson included:

- CREATE TABLE
- Data dictionary
- Table
- External table
- Schema
- DEFAULT

Summary

In this lesson, you should have learned how to:

- Categorize the main database objects
- Review a table structure
- Describe how schema objects are used
- Create a table using the appropriate data type for each column
- Explain the use of external tables
- Use the Data Dictionary to obtain the names and other attributes of database objects

